MAAOA/215-Series

TOGGLE SWITCHES

The MAAOA/215-Series toggle switches are single pole, AC rated at 20 amps and 125 VAC. These switches are snap-in mounted, with a phenolic toggle and base, and are suitable for high ambient temperature applications.









Product Highlights:

- · High temperature Phenolic base and toggle
- · Ratings to 125VAC
- · Optional embossed On-Off legend
- Choice of screw, .250 Tab or integrated wire lead connections

Typical Applications:

- · Coffee Makers
- Food Warmers





Dielectric Strength

UL/CSA: 1000V - live to dead metal parts & opposite polarity

Electrical Life

25,000 cycles

Operating Temperature

32°F to 185°F (0°C to 85°C)



1 BASE PART NUMBER: SERIES / CIRCUITRY / RATING /

10A 250 VAC, 20A 125 VAC, 1/2 HP 125-250 VAC

.250 Tabs Screw Terms. Wire Leads Single Pole On-Off


MAAOA 215 215A (On)-Off MM-021


Panel Cut-Out recommendations: For sheet metal panels, switch must enter panel in same direction as the punch. (Burr on bottom.) Test cut hole in actual material.

Imprinting is available. ON-OFF legend is not standard and must be specified after color. If not specified, switch will be manufactured with no legend.

- Indicates momentary function.







MOUNTING HOLE
Panel Thickness: .030[,762] min - .090 [2.28] max.
Specific cutout dimension range
dependent on panel thickness and material.



^{*}Manufacturer reserves the right to change product specification without prior notice.